

# FLPA-LED

## Construction:

- Steel housing and chassis
- Diffuser is White Frosted Acrylic or optional Clear Smooth Acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- ½" NPT knuckle mounts to junction box or ground fitter
- Optional Photocell (21)
- Optional Grid Louver (GL) reduces side glare
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Voltage 120 - 208 - 240 - 277
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### FLPA-5

Height - 4 ½"  
 Width - 8 ½"  
 Depth - 2 ½"



## ORDERING INFORMATION

Example: FLPA-5-LED-O2A16-4-Z1-WFA

### FLPA

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
5-LED	O2A16	16	2122	0-10v	NO	2 3000K		W1 Yolk	WFA White Frosted Acrylic	DIM LED dimming driver (0 - 10v)
						3 3500K		W2 Gloss White		
						4 4000K		W3 Text White		
						5 5000K		W13 Pearl Beige		
								CSA Clear Smooth Acrylic		
										21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt  24 24" Extension Arms 84 Ground Fitter GL Grid Louver FH Fixed Hood



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

