

DENW-LED

Construction:

- Steel housing and chassis
- Clear prismatic polycarbonate lens behind shield

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots left and right
- Optional knockouts (KO) top and bottom
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



DENW-10

Height - 10"
Width - 13.25"
Depth - 8.25"

DENW-14

Height - 14"
Width - 17"
Depth - 11"



ORDERING INFORMATION

Example: DENW-14-LED-O4A-2-Z1

DENW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige		DIM LED dimming driver (0 - 10v)
10-LED	O2A	12	1600	0-10v	NO	Optional 3 3500K				90CRI Consult Factory
14-LED	O2A	12	1600	0-10v	NO					42 All Aluminum Construction
	O4A	24	3200	0-10v	NO					Optional Voltage -347V Input voltage to 347v
										Battery Backup Options (Available with 0-10v only) (Excludes DENW-10) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

