

# FWXA-LED

## Construction:

- Aluminum housing and chassis
- Diffuser is Clear Smooth Acrylic or optional White Frosted Acrylic

## Light Source:

- LED
- Dimming to 10%

## Notes:

- ½" NPT knuckle mounts to junction box or ground fitter
- Photocell (21) – specify voltage 120v or 277v
- GL (Grid Louver) reduces side glare
- FWXA-5 and 15 come standard with (1) knuckle – use option 2K for additional knuckle
- Optional Extension arms to match finish
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Voltage 120 - 208 - 240 - 277
  - 5-Year Warranty on LED Components

<b>Type:</b>	
<b>Job Name:</b>	



<b>FWXA-5</b>	<b>FWXA-15</b>
Height - 5"	Height - 5"
Width - 9¼"	Width - 14¼"
Depth - 7"	Depth - 7"



## ORDERING INFORMATION

**Example: FWXA-5-LED-O2A-4-P3-CSA-24**

### FWXA

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
5-LED	O1A	6	800	0-10v	NO	2 3000K 3 3500K		P3 Clear Anodized Aluminum	CSA Clear Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory
	O2A	12	1600	0-10v	NO	4 4000K 5 5000K		Optional (See Price List)	Optional (See Price List)	90CRI Consult Factory
15-LED	O2A	12	1600	0-10v	NO			W1 Yolk W2 Gloss White W3 Text White B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WFA White Frosted Acrylic	21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt  24 24" Extension Arms 84 Ground Fitter GL Grid Louver TM Trunnion Mount 2K (2) Knuckles FH Fixed Hood



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

