

LTCW-LED

Construction:

- Steel chassis
- Diffuser is a white smooth acrylic lens with a top and bottom lens.
- Lens is offset from wall 1/2"

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	




LTCW-12-LED

Dim 'A' - 12" - 16" - 26"

Dim 'B' - 7 3/4"

Dim 'C' - 4"

Dim 'MC' - 6" - 8" - 13"



ORDERING INFORMATION

Example: **LTCW-16-LED-F1J-4-T6-WSA**

LTCW

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Accent / Options
12-LED	O2B	15	2000	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1O	10	863	TRIAC/ELV	YES			M13 Anod Silver		
	F1P	15	1361	TRIAC/ELV	YES			T4 Shimmer Gray		
16-LED	O2C	18	2420	0-10v	NO			T6 Pewter		ES Energy Star listed components T24 Title 24/JA8 Compliant (F10 & F1P configuration only)
	F1P	15	1361	TRIAC/ELV	YES			W2 Gloss White		
	F1J	20	2820	0-10v	YES			W1 Yolk White		
26-LED	O2C	18	2420	0-10v	NO			Z1 Satin Bronze		
								Z3 Text Bronze		
								Optional Finishes (see Price List)		
								M17 Brass Powder		
								P2 Brushed Alum		
										Battery Backup Options (Available with 0-10v dimming only) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
www.lightwayind.com • sales@lightwayind.com

