

OAKW-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster acrylic lenses

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Closed top eliminates upward light pollution
- Optional battery backup
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



OAKW-13

Height - 13"
Width - 7 1/4"
Depth - 4"

OAKW-15

Height - 14 3/4"
Width - 8 1/4"
Depth - 4"

OAKW-18

Height - 19 5/8"
Width - 11"
Depth - 6"



ORDERING INFORMATION

Example: OAKW-18-LED-O2C-4-Z1-WTP

OAKW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
13-LED	F1O	10	863	TRIAC/ELV	YES	2 3000K 3 3500K 4 4000K		B1 Satin Black	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1P	15	1361	TRIAC/ELV	YES			Z1 Satin Bronze		
	F1H	9	1400	0-10v	YES			Z3 Text Bronze		
	F1J	20	2820	0-10v	YES			W1 Yolk White		
15-LED	F1H	9	1400	0-10v	YES			W2 Gloss White	Optional Lens Material (See Price List)	T24 Title 24/JA8 Compliant (F10 & F1P configuration only) ES Energy Star listed components
	F1P	15	1361	TRIAC/ELV	YES			W3 Text White		
	O2B	15	2000	0-10v	NO			T4 Shimmer Gray		
18-LED	F1H	9	1400	0-10v	YES			M13 Anod Silver	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate	16 Bottom Lens 21 Photocell - See Notes -01 120 volt -02 277 volt
	O2C	18	2420	0-10v	NO			T6 Pewter		
								W13 Pearl Beige		
								Optional (See Price List)		
								M17 Brass Powder		Battery Backup Options (Available with O2B & O2C only) (OAKW-15 & 18 only) BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

