

MDNW-LED

Construction:

- Aluminum housing and chassis
- White Smooth Acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots left and right
- All aluminum construction (painted finish only)
- Optional battery backup
- Optional Photocell (-21)
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



MDNW-16

Height - 16"

Width - 11"

Depth - 10 3/4"



ORDERING INFORMATION

Example: MDNW-16-LED-04C-4-B2-WSA

MDNW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) 21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt 90CRI Consult Factory Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
16-LED	O3C	27	3630	0-10v	NO	Optional 3 3500K				
	O4C	36	4840	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

