

# DTPW-LED

## Construction:


- Steel housing and chassis
- Diffuser is .080" thick white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster lenses are .080" thick acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup – hardware included
- Closed top eliminates upward light pollution
- Standard bottom lens
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components



Type:	
Job Name:	



## ORDERING INFORMATION

Example: DTPW-16-LED-F1H-4-B1-WTP

### DTPW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>W3</b> Text White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige	<b>WTP</b> White Textured Polycarbonate  <b>Optional Lens Material</b> (See Price List)  <b>AHA</b> Amber Honey Alabaster <b>BAA</b> Beige Alabaster <b>OAA</b> Opal Alabaster <b>WSP</b> White Smooth Polycarbonate	<b>DIM</b> LED dimming driver (0 - 10v)  <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page <b>90CRI</b> Consult Factory  <b>ES</b> Energy Star listed components <b>21</b> Photocell - <i>See Notes</i> -01 120 volt -02 277 volt  Optional Voltage -347V Input voltage to 347v
<b>16-LED</b>	<b>F1O</b>	10	863	TRIAC/ELV	YES	<b>Optional</b> 3 3500K		<b>W17</b> Brass Powder  <b>Optional</b> (See Price List)		
	<b>F1P</b>	15	1361	TRIAC/ELV	YES					
	<b>F1H</b>	9	1400	0-10v	YES					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

