

MACC-LED

Construction:

- Steel housing and chassis
- Diffuser is white smooth polycarbonate.
- Optional alabaster lenses are .080" thick acrylic

Lamps:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



MACC-12

Height - 6"
 Width - 11 1/2"
 Length - 7 1/2"



ORDERING INFORMATION

Example: MACC-12-LED-F1L-4-Z3-WTP

MACC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder	WSP White Smooth Polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v)
12-LED	F1L	9	1400	0-10v	YES	Optional 3 3500K				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

