

TLOW-LED

Construction:

- Steel housing and chassis
- Clear Smooth Acrylic Lens
- Optional White Frosted Acrylic Lens


Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate
- All aluminum construction (painted finish only)
- Optional photocell - (21) specify voltage 120v or 277v
- Optional battery backup
- Dark Sky compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



TLOW-8-LED

Height - 8"
Width - 8 1/4"
Depth - 6"

TLOW-10-LED

Height - 10"
Width - 10 1/4"
Depth - 7 1/4"

TLOW-12-LED

Height - 13 3/4"
Width - 12 1/4"
Depth - 8 1/2"



ORDERING INFORMATION

Example: TLOW-10-LED-O2A-4-W2-WSA-42

TLOW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
8-LED	O1A	6	800	0-10v	NO	1 2700K 2 3000K 3 3500K 4 4000K 5 5000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder P2 Brushed Alum	CSA Clear Smooth Acrylic WFA White Frosted Acrylic	DIM LED dimming driver (0 - 10v) 42 All Aluminum Construction 21 Photocell - <i>See Notes</i> -01 120 volt -02 277 volt OCCHFA Concealed Occupancy Sensor Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	O2A	12	1600	0-10v	NO					
10-LED	O1A	6	800	0-10v	NO					
	O2A	12	1600	0-10v	NO					
12-LED	O1B	8	1000	0-10v	NO					
	O2B	15	2000	0-10v	NO					
	O3B	22	3000	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

