

ACNW-LED

Construction:

- Steel housing, chassis and top
- Diffuser is .080" thick white textured polycarbonate or optional white smooth polycarbonate

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; Keyhole slots left and right
- Custom cage styles available
- Solid steel top; front and down light only
- Optional clear acrylic bottom lens
- ADA compliant
- UL and CUL listed **WET** location



Cage B



Cage C



Cage D

Type:	
Job Name:	



Cage A

ACNW-12

Height - 12"
Width - 12"
Depth - 4"



ORDERING INFORMATION

Example: ACNW-12-LED-A-F1P-4-T4-WSP

ACNW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	F1H	9	1400	0-10v	YES	2 3000K 4 4000K	A B C D X	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate Optional Lens Material (see Price List) WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory BL Bottom Lens OCCHFB Concealed Occupancy Sensor (O2A Configuration Only) See Sensor Resource Sheet Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	F1O	10	863	TRIAC/ELV	YES	Optional 3 3500K		Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel		
	O2A	12	1600	0-10v	NO					
	F1P	15	1361	TRIAC/ELV	YES					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

