

# ATLW-LED

## Construction:

- Steel housing and chassis
- Diffuser is .10" thick extruded white acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup - hardware included
- Open top and bottom
- Horizontal or vertical mounting
- Optional battery backup
- ADA compliant
- UL and CUL listed DAMP location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components
- **For WET listed version see MANW Series**

<b>Type:</b>	
<b>Job Name:</b>	



### ATLW-16-LED

Height - 16"  
Width - 7 1/8"  
Depth - 4"

### ATLW-24-LED

Height - 24"  
Width - 7 1/8"  
Depth - 4"



## ORDERING INFORMATION

**Example: ATLW-16-LED-O2C-4-B1-WSA**

### ATLW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		<b>B1</b> Satin Black <b>M13</b> Anod Silver <b>T4</b> Shimmer Gray <b>T6</b> Pewter <b>W2</b> Gloss White <b>W1</b> Yolk White <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>P0</b> Polished Brass* <b>P1</b> Chrome* <b>P2</b> Brushed Alum	<b>WSA</b> White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v Consult Factory
<b>16-LED</b>	<b>O2C</b>	18	2420	0-10v	NO	<b>Optional</b> 3 3500K				<b>90CRI</b> Consult Factory
<b>24-LED</b>	<b>O2C</b>	18	2420	0-10v	NO					
<p style="text-align: right;">Optional Voltage <b>-347V</b> Input voltage to 347v</p> <p style="text-align: right;"><b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes</p>										



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

