

OTBW-LED

Construction:

- Perforated aluminum shield; aluminum chassis
- Support "fingers" top and bottom are milled aluminum
- Diffuser is white textured polycarbonate behind perforated shield

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots or center lockup for standard J-box
- Custom cage styles available
- Open top and bottom for up and down light
- Optional Battery Backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



OTBW-12-LED

Height - 11 1/2"
Width - 10 1/2"
Depth - 4 3/8"



ORDERING INFORMATION

Example: **OTBW-12-LED-F1H-4-T6-POS**

OTBW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K				
12-LED	F1H	9	1400	0-10v	YES	Optional 3 3500K		P2 Brushed Alum B1 Satin Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional <i>(See Price List)</i>	POS Small Perforated Steel Shield with White Textured Polycarbonate and Milled Aluminum Fingers Top and Bottom	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory Optional Voltage -347V Input voltage to 347v Battery Backup Options <i>(Available with 0-10v only)</i> BB10 10 Watts (1170lm) for 90-Minutes
	F1O	10	863	TRIAC/ELV	YES					
	F1P	15	1361	TRIAC/ELV	YES					
	F1J	20	2820	0-10v	YES					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

