PDSW-LED

Construction:
- Aluminum housing and chassis
- Bottom lens is white frosted or clear smooth acrylic, or optional clear prismatic

Light Source:
- LED
- Dimming to 10% **Included**

Notes:
- Center lockup – hardware include
- Optional J-Box with knockouts for surface conduit (39)
- Dark sky compliant
- ADA Compliant
- Optional Battery Backup increases depth to 4”
- **Build America, Buy America Act Compliant**
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



Shown with Clear Prismatic Lens

PDSW-5-LED
Height - 5 ⅛”
Width - 7 ⅛”
Depth - 3 ½”

PDSW-12-LED
Height - 5 ⅛”
Width - 12”
Depth - 3 ½”

ORDERING INFORMATION

Example: PDSW-5-LED-O1A-4-B1-CPA

PDSW [ ] [ ] [ ] [ ] [ ] [ ] [ ]

Size	LED	Watts	Source Lumens	Dimming	Energy Star
5-LED	O1A	6	800	0-10v	NO
	O1M	15	2050	0-10v	NO
12-LED	O1C	9	1210	0-10v	NO
	O2C	18	2420	0-10v	NO

Kelvin
2 3000K
3 3500K
4 4000K

Cage

Finish
B1 Satin Black
B2 Text Black
Z1 Satin Bronze
Z3 Text Bronze
W1 Yolk White
W2 Gloss White
T4 Shimmer Gray
M13 Anod Silver
T6 Pewter
W13 Pearl Beige

Optional
(See Price List)
M17 Gold Brass
P2 Brushed Alum
P9 Brushed Nickel

Diffuser
WFA White Frosted Acrylic
CSA Clear Smooth Acrylic

Optional Lens Material
(See Price List)

CPA Clear Prismatic Acrylic

Options
DIM LED dimming driver (0 - 10v)

21 Photocell - Spedify voltage
01 - 120 volt
02 - 277 volt

39 J-Box with Knockouts
(increases depth by 1 ¼”)

* **UP/DN** “Damp listing only”
(Up/Down Light)

Battery Backup Options
(Increases fixture depth to 4”)
BB10 10 Watts (1170lm) for 90-Minutes

28435 Industry Drive., Valencia, California 91355
800-325-4448 /661-257-0286
www.lightwayind.com • sales@lightwayind.com

Revision: 05/08/2026