

BPRH-LED

Construction:

- Steel top, bottom and rings
- Cylinder is .125" thick white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts standard "J-Box", hardware included
- Standard is 3' of chain with 6' of cord
- Optional single stem and 45-degree swivel
- Bottom of fixture is open; optional clear bottom lens or solid bottom cover (no down light)
- UL and CUL listed **DAMP** location
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



Shown with solid bottom cover

BPRH-12	BPRH-16	BPRH-21
Height - 12"	Height - 16"	Height - 21"
Width - 7 1/4"	Width - 8 1/2"	Width - 10"
OAH - 36"	OAH - 36"	OAH - 48"



ORDERING INFORMATION

Example: BPRH-16-LED-O4C-4-Z3-WSP-CHN-BSJ-36"OAH-SSB

BPRH

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
12-LED	O4B	29	4000	0-10v	NO	2 3000K 4 4000K Optional 3 3500		B1 Satin Black B2 Text Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W1 Yolk W2 Gloss White W3 Text White W13 Pearl Beige Z1 Satin Bronze Z3 Text Bronze	WSA White Smooth Acrylic	(Suspension Systems) Please list Over All Height CFM Ceiling Flush Mount 1SLM45 -Single Stem 45 degree swivel CHN -____ - 3' of chain and 6' cord (STD) WSJ - White "SJ" Cord BSJ - Black "SJ" Cord DIM LED dimming driver (0 - 10v) 90CRI Consult Factory CBL Clear Bottom Lens SSB Solid Bottom Cover
	1E26		0	TRIAC/ELV	NO					
16-LED	O4C	36	4840	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					
21-LED	O8B	58	8000	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

