

Type:	
Job Name:	

Construction:

- Spun Aluminum Side cover
- Laser Cut Acrylic lens

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to a standard J-box
- Down Light only
- UL and CUL listed **DAMP** location
- Field Adjustable Aircraft Cable and SO Cord
- LED Components
 - Replaceable Module
 - CRI > 80, Optional CR > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components
- See RKTC for matching flush ceiling mount



Shown with optional decorative knobs (DS)



RKTH-24

Fixture Height - 4.5"
 Diameter - 24"
 Overall Height - 24"

Example: RKTH-24-LED-L1A-4-G3-WFA-3AC-24"OAH

RKTH

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black G3 Dark Green R1 Red U10 Bengal Blue Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WFA White Frosted Acrylic	DIM LED dimming driver (0 - 10v) 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> Optional Voltage -347V Input voltage to 347v DS Decorative knobs Battery Backup Options <i>(Available with 0-10v only)</i> BB10 10 Watts (1170lm) for 90-Minute
24-LED	L1A	36	4000	0-10v	NO	Optional 3 3500K		Optional (See Price List) M17 Brass Powder		
24-LED	O8C	72	9680	0-10v	NO					

