

# GBGW-LED

## Construction:

- Polycarbonate housing
- Diffuser is frosted smooth polycarbonate

## Light Source:

- LED
- Line Dimming **Included**

## Notes:

- Mounts to standard junction box
- Center lockup
- Vandal Resistant
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - 120 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



## GBGW-10

Diameter - 10 1/4"

Depth - 5"



## ORDERING INFORMATION

Example: GBGW-10-LED-F10-4-W99-WFP

## GBGW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B99 Black W99 White	FSP Frosted Smooth Polycarbonate	DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
10-LED	J1A	13	900	TRIAC/ELV	YES					ES Energy Star listed components 90CRI Consult Factory



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

