

PDLW-LED

Construction:

- Steel housing and chassis
- Bottom lens is white frosted acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Dark sky compliant
- Wall mount only
- Down light only
- ADA Compliant
- Optional **LBC** large box cover to mount to standard extension box
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PDLW-24-LED

Height - 3"
Width - 24"
Depth - 2"

PDLW-36-LED

Height - 3"
Width - 36"
Depth - 2"

PDLW-47-LED

Height - 3"
Width - 47"
Depth - 2"

Mounts to 2 x 4 box/opening oriented to match fixture's linear dimension



ORDERING INFORMATION

Example: **PDLW-36-LED-O3C-4-T4-WSA**

PDLW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
24-LED	O2C	18	2420	0-10v	NO	2 3000K		B1 Satin Black	WFA White Frosted Acrylic	LBC Large box cover standard junction box (5" wide x 6" high)
						3 3500K		B2 Text Black		
						4 4000K		Z1 Satin Bronze		
						5 5000K		Z3 Text Bronze		
36-LED	O3C	27	3630	0-10v	NO		W1 Yolk White			
47-LED	O4C	36	4840	0-10v	NO		W2 Gloss White			
							T4 Shimmer Gray			
							M13 Anod Silver			
							T6 Pewter			
							W13 Pearl Beige			
							Optional (See Price List)			
							M17 Brass Powder		Battery Backup Options	
							P2 Brushed Alum		BB10 Battery backup unit providing 8 Watts (1170lm) for 90-Minute	
							P9 Brushed Nickel			



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
www.lightwayind.com • sales@lightwayind.com

