

# SDGP-LED

## Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate
- Optional alabaster acrylic lenses

## Light Source:

- LED

## Notes:

- Mounts to 3" round pole – fitter included
- Fixture dimensions excluded fitter
- See supplemental spec sheet on website for pole options
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### SDGP-13-LED

Height - 13"  
Width - 9"  
Depth - 9"

### SDGP-22-LED

Height - 22"  
Width - 12"  
Depth - 12"



## ORDERING INFORMATION

Example: SDGP-13-LED-O4C-4-B1-WTP

### SDGP

Size	LED					Kelvin	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K			Optional Voltage -347V Input voltage to 347v
13-LED	1E26		0	TRIAC/ELV	NO	Optional 3 3500K	<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>W3</b> Text White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  Optional (See Price List) <b>M17</b> Brass Powder <b>M16</b> Antique Brass	<b>WTP</b> White Textured Polycarbonate  <b>Optional Lens Material</b> (See Price List)  <b>AHA</b> Amber Honey Alabaster <b>BAA</b> Beige Alabaster <b>OAA</b> Opal Alabaster	<b>Pole Options</b> (see supplemental spec sheet on website and price list)
	O4B	29	4000	0-10v	NO				
	O4C	36	4840	0-10v	NO				
22-LED	O4C	36	4840	0-10v	NO				
	O8C	72	9680	0-10v	NO				



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

