

NDTW-LED

Construction:

- Steel housing and chassis
- Bottom lens, see below

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate
- Optional photocell (21)
- Optional all aluminum construction (painted finishes only)
- Dark sky compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

| | |
|-----------|--|
| Type: | |
| Job Name: | |



NDTW-14

Height - 14"

Width - 24"

Depth - 15"



ORDERING INFORMATION

Example: **NDTW-14-LED-O1M-4-T4-CEG**

NDTW

| Size | LED | | | | | Kelvin | Cage | Finish | Diffuser | Options |
|--------|-----|-------|---------------|---------|-------------|-------------------------------|------|---|---|---|
| | | Watts | Source Lumens | Dimming | Energy Star | | | | | |
| 14-LED | O2A | 12 | 1600 | 0-10v | NO | 2 3000K 3 3500K 4 4000K | | B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige | CEG Clear Tempered Glass WSA White Smooth Acrylic CSA Clear Smooth Acrylic WFA White Frosted Acrylic | DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page 21 Photocell - See Notes -01 120 volt -02 277 volt 42 All Aluminum Construction T24 Title 24/JA8 Compliant Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes |
| | O1M | 15 | 2050 | 0-10v | NO | | | | | |



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

