

# PLVH-LED

**Construction:**

- Steel housing and chassis
- Bowl is frosted smooth glass
- Optional white smooth acrylic or alabaster acrylic bowl

**Light Source:**

- LED
- Dimming to 10% **Included**


**Notes:**

- Canopy mounts to J-Box with integral safety cable
- Tri-Pod with hub and chain is standard
- Custom mounting heights available
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



	PLVH-17	PLVH-21
A	5"	7"
B	19 1/2"	19 1/2"
C	16 1/2"	16 1/2"
OAH	41"	47"
D	16 1/2"	20 1/2"



## ORDERING INFORMATION

**Example: PLVH-21-LED-F1Q-4-T6-FSG-DIM**

**PLVH**

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
17-LED	F1L	9	1400	0-10v	YES	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	FSG Frosted Smooth Glass  Optional Lens Material (see Price List)	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page  ES Energy Star listed components T24 Title 24/JA8 Compliant (F1P & F1Q configuration only)  90CRI Consult Factory  OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet  Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	F1K	13	2115	0-10v	YES	Optional 3 3500				
	O3B	22	3000	0-10v	NO					
	L1A	36	4000	0-10v	NO					
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					
21-LED	F1K	13	2115	0-10v	YES		Optional (See Price List) M17 Brass Powder			
	L1A	36	4000	0-10v	NO					
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

