

VEGC-LED

Construction:

- Steel pan with stamped steel motif accent band
- Diffuser is frost smooth glass or optional white acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Canopy mounts to standard J-Box
- Optional battery backup
- UL and CUL listed DAMP location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



VEGC-15

Height - 8 1/4"

Diameter - 15 1/4"



ORDERING INFORMATION

Example: VEGC-15-LED-F1M-4-Z3-FSG

VEGC

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
15-LED	F1L	9	1400	0-10v	YES	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	FSG Frosted Smooth Glass Optional Lens Material (see Price List) WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLED Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	F1O	10	863	TRIAC/ELV	YES	Optional 3 3500		Optional (See Price List) M17 Brass Powder M16 Antique Brass		
	F1P	15	1361	TRIAC/ELV	YES					
	F1K	13	2115	0-10v	YES					
	F1Q	23	2057	TRIAC/ELV	YES					
	1E26		0	TRIAC/ELV	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

