

# CLLC-LED

## Construction:

- Diffuser is white smooth acrylic with bonded linen side trim

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 ¾" extension ring
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	




BLA  
Black Linen Acrylic



CTA Chocolate  
Linen Acrylic



RTA  
Rapid Linen Acrylic



WLA  
White Linen Acrylic

### CLLC-11-LED

Height - 3"  
Diameter - 11"

### CLLC-14-LED

Height - 3 ½"  
w/ext ring - 5 ¼"  
Diameter - 14"



## ORDERING INFORMATION

Example: CLLC-14-LED-F1Q-4-W2-SLA-ES

## CLLC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		W2 Gloss White		
11-LED	F1L	9	1400	0-10v	YES			WLA White Linen Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page  <b>EXT</b> Extended housing (adds 2 inches /match BB10) <b>42</b> Aluminum Pan (11" & 14" only) <b>ES</b> Energy Star listed components <b>T24</b> Title 24/JA8 Compliant (F10, F1P & F1Q configuration only) <b>OCCHFA</b> Concealed Occupancy Sensor See Sensor Resource Sheet  <b>Battery Backup Options</b> (Requires 1 ¾" extension ring) (Available with 0-10v only) <b>CLLC-14 and 19 only</b> <b>BB10</b> 10 Watts (1170lm) for 90-Minutes	
	F1O	10	863	TRIAC/ELV	YES			CTA Chocolate Linen Acrylic		
	F1P	15	1361	TRIAC/ELV	YES			SLA Sable Linen Acrylic		
14-LED	F1K	13	2115	0-10v	YES			RTA Rapid Linen Acrylic		
	F1P	15	1361	TRIAC/ELV	YES			BTA Black Linen Acrylic		
	F1Q	23	2057	TRIAC/ELV	YES					



28435 Industry Drive., Valencia, California 91355  
 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 www.lightwayind.com • sales@lightwayind.com

