

PLVC-LED

Construction:

- Steel pan
- Diffuser is frosted smooth glass

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-Box installation
- Optional Battery Backup
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PLVC-17
Height - 5 1/4"
Diameter 16 1/2"

PLVC-21
Height - 7"
Diameter 20 3/4"



ORDERING INFORMATION

Example: PLVC-21-LED-F1Q-4-T6-FSG

PLVC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options				
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K			FSG Frosted Smooth Glass					
17-LED	F1L	9	1400	0-10v	YES	Optional 3 3500		B1 Satin Black	FSG Frosted Smooth Glass	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See <i>Sensor Resource Sheet</i> Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes				
	F1K	13	2115	0-10v	YES			B2 Text Black						
	O3B	22	3000	0-10v	NO			Z1 Satin Bronze						
	L1A	36	4000	0-10v	NO			Z3 Text Bronze						
	F1P	15	1724	TRIAC/ELV	YES			W1 Yolk White						
	F1Q	23	2540	TRIAC/ELV	YES			W2 Gloss White						
21-LED	F1K	13	2115	0-10v	YES			T4 Shimmer Gray						
	L1A	36	4000	0-10v	NO			M13 Anod Silver						
	F1P	15	1724	TRIAC/ELV	YES			T6 Pewter						
	F1Q	23	2540	TRIAC/ELV	YES			W13 Pearl Beige						
											Optional (See Price List)			
											M17 Brass Powder			
							M16 Antique Brass							
							P7 Brushed Steel							
							P9 Brushed Nickel							

28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

