

# VTCV-LED

## Construction:

- Steel chassis and end caps
- Diffuser is white smooth acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Mounts to standard J-Box with slotted anchor holes
- Optional battery backup
- Vertical or Horizontal mounting
- ADA compliant
- Optional independent nightlight circuit -Uplight only circuit
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



Length - 24" - 36" - 48" - 60" - 72"

Height - 4 1/4"

Depth - 3"



## ORDERING INFORMATION

Example: VTCV-36-LED-O3B-2-W1-WSA

VTCV

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
24-LED	O2B	15	2000	0-10v	NO	2 3000K 4 4000K	<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>W3</b> Text White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder	WSA White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page  <b>ES</b> Energy Star listed components <b>T24</b> Title 24/JA8 Compliant (F1Y configuration only) <b>90CRI</b> Consult Factory  <b>OCCHFA</b> Concealed Occupancy Sensor See <i>Sensor Resource Sheet</i>  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minute	
	F1Y	30	3235	TRIAC/ELV	YES					
36-LED	O3B	22	3000	0-10v	NO	Optional 3 3500K				
48-LED	O4B	29	4000	0-10v	NO					
72-LED	O6C	54	7260	0-10v	NO					
96-LED	O8C	72	9680	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com



Revision: 09/09/2021