

# LURW-LED

## Construction:

- Steel housing and chassis
- Diffuser is Translucent Bonded Linen Material available in a variety of color options





## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Universal mounting plate hardware included
- Custom cage styles available consult factory
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



Height - 25"  
 Width - 7 1/2"  
 Depth - 4"  
 MC - 12 1/2"



## ORDERING INFORMATION

Example: LURW-LED-A-F1G-4-M13-WLA

## LURW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K	A  X	B1 Satin Black B2 Text Black  Z1 Satin Bronze Z3 Text Bronze W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WLA White Linen Acrylic	DIM LED dimming driver (0 - 10v)  ES Energy Star listed components 90CRI Consult Factory
24-LED	F1G	15	2350	DIM or DIMLD	NO	Optional 3 3500K		Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	Optional Trim Options (Consult Factory) RTA Rapid Textured Acrylic BTA Black Textured Acrylic CTA Chocolate Textured Acrylic	



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

