

SYZW-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster acrylic lenses

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Closed top eliminates upward light pollution
- Optional battery backup
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SYZW-12	SYZW-15	SYZW-22
Height - 12"	Height - 13 ¾"	Height - 20 ½"
Width - 8"	Width - 10"	Width - 15"
Depth - 5 ¼"	Depth - 5 ½"	Depth - 7 ½"



ORDERING INFORMATION

Example: SYZW-22-LED-O2C-4-Z1-WTP

SYZW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K				
12-LED	F1H	9	1400	0-10v	YES	Optional 3 3500K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIML D Line Voltage /TRIAC/ELV/120v See Resource Page 90CRI Consult factory ES Energy Star listed components 16 Bottom Lens 21 Photocell - See Notes -01 120 volt -02 277 volt Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
	F1O	10	863	TRIAC/ELV	YES					Optional Lens Material (See Price List)
	F1P	15	1361	TRIAC/ELV	YES			AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate		
	F1J	20	2820	0-10v	YES			Optional (See Price List)		
15-LED	F1H	9	1400	0-10v	YES			M17 Brass Powder M16 Antique Brass		
	F1O	10	863	TRIAC/ELV	YES					
	O2B	15	2000	0-10v	NO					
	F1P	15	1361	TRIAC/ELV	YES					
	F1J	20	2820	0-10v	YES					
22-LED	F1H	9	1400	0-10v	YES					
	O2C	18	2420	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

