

# VTEV-LED

## Construction:

- Steel chassis and end caps
- Diffuser is white smooth acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Mounts to standard J-Box with slotted anchor holes
- Optional battery backup
- Vertical or Horizontal mounting
- ADA compliant
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

|           |  |
|-----------|--|
| Type:     |  |
| Job Name: |  |



Length - 24" - 36" - 48" - 60" - 72" - 96"  
 Height - 4 1/4"  
 Depth - 3"



## ORDERING INFORMATION

Example: VTEV-36-LED-L3B-2-W1-WSA

### VTEV

| Size   | LED |       |               |           |             | Kelvin                        | Cage | Finish                                                                                                                                                                                                                                                                                                                                            | Diffuser                        | Options                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------|-----|-------|---------------|-----------|-------------|-------------------------------|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        |     | Watts | Source Lumens | Dimming   | Energy Star |                               |      |                                                                                                                                                                                                                                                                                                                                                   |                                 |                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 24-LED | O2B | 15    | 2000          | 0-10v     | NO          | 2 3000K<br>3 3500K<br>4 4000K |      | <b>B1</b> Satin Black<br><b>B2</b> Text Black<br><b>Z1</b> Satin Bronze<br><b>Z3</b> Text Bronze<br><b>W1</b> Yolk White<br><b>W2</b> Gloss White<br><b>W3</b> Text White<br><b>T4</b> Shimmer Gray<br><b>M13</b> Anod Silver<br><b>T6</b> Pewter<br><b>W13</b> Pearl Beige<br><br><b>Optional</b><br>(See Price List)<br><b>M17</b> Brass Powder | <b>WSA</b> White Smooth Acrylic | <b>DIM</b> LED dimming driver (0 - 10v)<br><b>DIMLD</b> Line Voltage /TRIAC/ELV/120v<br>See Resource Page<br><br><b>ES</b> Energy Star listed components<br><b>T24</b> Title 24/JA8 Compliant<br>(F1Y configuration only)<br><br><b>OCCHFA</b> Concealed Occupancy Sensor<br>See Sensor Resource Sheet<br><br><b>Battery Backup Options</b><br>(Available with 0-10v only)<br><b>BB10</b> 10 Watts (1170lm) for 90-Minute |
|        | F1Y | 30    | 3235          | TRIAC/ELV | YES         |                               |      |                                                                                                                                                                                                                                                                                                                                                   |                                 |                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 36-LED | O3B | 22    | 3000          | 0-10v     | NO          |                               |      |                                                                                                                                                                                                                                                                                                                                                   |                                 |                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 48-LED | O4B | 29    | 4000          | 0-10v     | NO          |                               |      |                                                                                                                                                                                                                                                                                                                                                   |                                 |                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 72-LED | O6C | 54    | 7260          | 0-10v     | NO          |                               |      |                                                                                                                                                                                                                                                                                                                                                   |                                 |                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 96-LED | O8C | 72    | 9680          | 0-10v     | NO          |                               |      |                                                                                                                                                                                                                                                                                                                                                   |                                 |                                                                                                                                                                                                                                                                                                                                                                                                                           |



28435 Industry Drive., Valencia, California 91355  
 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 www.lightwayind.com • sales@lightwayind.com

