

TWXW-LED

Construction:

- Steel housing and chassis
- Diffuser is white frosted acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Photocell (increases depth by 1") – specify voltage
- ADA compliant
- UL and CUL listed **DAMP** location
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



TWXW-13

Height - 13 ¼"

Width - 4 ½"

Depth - 3 ½"



ORDERING INFORMATION

Example: TWXW-13-LED-01C-3-W1-WFA

TWXW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
13-LED	01C	9	1210	0-10v	NO	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List)	WFA White Frosted Acrylic	DIM LED dimming driver (0 - 10v) <i>(Included with On Board Driver only)</i> 21 Photocell - See Notes -01 120 volt -02 277 volt 42 All Aluminum Construction



28435 Industry Drive., Valencia, California 91355
 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 www.lightwayind.com • sales@lightwayind.com

