

# PMLH-LED

## Construction:

- Steel housing and chassis
- Elliptical white smooth acrylic bowl is standard
- Optional alabaster bowl

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Canopy mounts to J-Box with integral safety cable
- Custom mounting heights available
- Single stem with aircraft cable (1S454AC) suspension with 45-degree swivel (Standard)
- Single (1R) or Double (2R) Ring option
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

|           |  |
|-----------|--|
| Type:     |  |
| Job Name: |  |



### PMLH-24-LED

Height - 7"  
Width - 24"  
OAH - 24"

### PMLH-36-LED

Height - 10"  
Width - 36"  
OAH - 36"



## ORDERING INFORMATION

**Example: PMLH-36-LED-O12C-4-Z1-WSA-1S454AC-36OAH**

## PMLH

| Size   | LED  |       |               |         |             | Kelvin             | Rings    | Finish  | Diffuser   | Options  |
|--------|------|-------|---------------|---------|-------------|--------------------|----------|---|--|--|
|        |      | Watts | Source Lumens | Dimming | Energy Star | 2 3000K<br>4 4000K | 1R<br>2R | B1 Satin Black<br>B2 Text Black<br>Z1 Satin Bronze<br>Z3 Text Bronze<br>W1 Yolk White<br>W2 Gloss White<br>T4 Shimmer Gray<br>M13 Anod Silver<br>T6 Pewter<br>W13 Pearl Beige | WSA WhiteSmooth Acrylic<br><br><b>Optional Lens Material</b><br>(see Price List)<br><br>AHA Amber Honey Alabaster<br>BAA Beige Alabaster<br>OAA Opal Alabaster | <b>(Suspension Systems)</b><br>Please list <b>Over All Height</b><br><b>1SLM45</b> - Single Stem 45 degree swivel<br><b>1S454AC</b> - Single Stem 45 degree swivel w/Aircraft Cable (Standard)<br><b>4S</b> - Four Stem<br><b>1S4AC</b> - Single Stem with 4 Aircraft Cable<br><br><b>DIM</b> LED dimming driver (0 - 10v)<br><b>DIMLD</b> Line Voltage /TRIAC/ELV/120v<br>Consult Factory<br><br><b>90CRI</b> Consult Factory<br><br><b>Battery Backup Options</b><br>(Available with 0-10v only)<br><b>BB10</b> 10 Watts (1170lm) for 90-Minutes |
| 24-LED | L1A  | 36    | 4000          | 0-10v   | NO          | Optional<br>3 3500 |          |   |  |  |
|        | O6C  | 54    | 7260          | 0-10v   | NO          |                    |          |   |  |  |
|        | O8C  | 72    | 9680          | 0-10v   | NO          |                    |          |   |  |  |
|        | O9C  | 80    | 10890         | 0-10v   | NO          |                    |          |   |  |  |
| 36-LED | L1A  | 36    | 4000          | 0-10v   | NO          |                    |          |   |  |  |
|        | O6C  | 54    | 7260          | 0-10v   | NO          |                    |          |   |  |  |
|        | O8C  | 72    | 9680          | 0-10v   | NO          |                    |          |   |  |  |
|        | O12C | 107   | 14520         | 0-10v   | NO          |                    |          |   |  |  |
|        | O18C | 160   | 21780         | 0-10v   | NO          |                    |          |   |  |  |



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

