

RERH-LED

Construction:

- Steel housing and chassis
- Diffuser is white smooth acrylic
- Optional alabaster acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Canopy mounts to J-Box with integral safety cable
- Custom mounting heights available
- Single stem (1S45) 45-degree swivel standard
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



Shown with 4 Stem and optional AHA Diffuser



IS45

RERH-24-LED	RERH-30-LED	RERH-36-LED
Height - 6"	Height - 8"	Height - 8"
OAH - 24"	OAH - 30"	OAH - 36"
Width - 24.75"	Width - 30"	Width - 36"



ORDERING INFORMATION

Example: RERH-24-LED-L12B-4-Z1-AHA-1S45-OAH24

RERH

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K			WSA White Smooth Acrylic	(Suspension Systems) Please list Over All Height
24-LED	L1A	36	4000	0-10v	NO	Optional 3 3500K		B1 Satin Black	Optional Lens Material (see Price List)	IS45 -Single Stem 45 degree swivel 4S Four Stem 1S154AC - Single Stem w/Aircraft Cable 4AC__ - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord
	O6C	54	7260	0-10v	NO			B2 Text Black		
	O8C	72	9680	0-10v	NO			Z1 Satin Bronze		
	O9C	80	10890	0-10v	NO			Z3 Text Bronze		
	O12C	107	14520	0-10v	NO			W1 Yolk White		
30-LED	L1A	36	4000	0-10v	NO			W2 Gloss White	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	Optional LED dimming driver (0 - 10v) 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet
	O6C	54	7260	0-10v	NO			T4 Shimmer Gray		
	O8C	72	9680	0-10v	NO			M13 Anod Silver		
	O9C	80	10890	0-10v	NO			T6 Pewter		
	O12C	107	14520	0-10v	NO			W13 Pearl Beige		
36-LED	O16C	143	19360	0-10v	NO	Optional (See Price List)	M17 Brass Powder	Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute		
	O18C	160	21780	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

