

ARCC-LED

Construction:

- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- Optional battery backup - Requires 1 3/4" extension ring (14" & 19" only)
- **Build America, Buy America Act Compliant**
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI >90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



ARCC-11-LED	ARCC-14-LED	ARCC-19-LED
Height - 3"	Height - 3 1/2"	Height - 3 3/8"
Diameter - 11"	w/ext ring - 5 1/4"	w/ext ring - 5 1/4"
	Diameter - 14"	Diameter - 19"



ORDERING INFORMATION

Example: ARCC-14-LED-F1P-4-W2-WSA-ES

ARCC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
11-LED	F1L	9	1400	0-10v	YES	2 3000K 3 3500K 4 4000K		B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1O	10	863	TRIAC/ELV	YES			Z1 Satin Bronze		
	F1P	15	1361	TRIAC/ELV	YES			Z3 Text Bronze		
14-LED	F1K	13	2115	0-10v	YES			W1 Yolk White	Optional Lens Material (see Price List) WSAHE White Smooth Acrylic High Efficiency	42 Aluminum Pan (11" & 14" only) ES Energy Star listed components KO Extension ring w/knockout T24 Title 24/JA8 Compliant (F10 & F1P configuration only) OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet
	F1P	15	1361	TRIAC/ELV	YES			T4 Shimmer Gray		
	F1Q	23	2057	TRIAC/ELV	YES			M13 Anod Silver		
19-LED	L1A	36	4000	0-10v	NO			T6 Pewter		
								W13 Pearl Beige		
								Optional (See Price List) M17 Brass Powder		Battery Backup Options (Requires 1 3/4" extension ring) (Available with 0-10v only) ARCC-14 and 19 only BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
www.lightwayind.com • sales@lightwayind.com

