

# CBTB-LED

## Construction:

- Corrosion resistant coated steel housing and chassis
- Diffuser is white textured polycarbonate
- Optional alabaster lenses

## Lamps:

- Dedicated LED
- Dimming to 10% **Included**

## Notes:

- Mounts to top of Pier/Corner Stone/Pilaster
- Hole for center conduit
- Custom sizes available
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



**CBTB-12**  
 Height - 10"  
 Width - 12"  
 Length - 12"

**CBTB-16**  
 Height - 11"  
 Width - 16"  
 Length - 16"



## ORDERING INFORMATION

Example: CBTB-12-LED-F1L-4-Z3-WTP

### CBTB

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Deliver Lumens	Dimming	Energy Star					
12-LED	F1L	9	1400	0-10v	YES	2 3000K 4 4000K	<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder	<b>WTP</b> White Textured Polycarbonate  <b>Optional Lens Material</b> (See Price List)	<b>DIM</b> LED dimming driver (0 - 10v)  <b>ES</b> Energy Star listed components  <b>42</b> Aluminum construction  <b>21</b> Photocell - Specify voltage 01 - 120 volt 02 - 277 volt  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes	
	O4A	24	3200	0-10v	NO					
	1E26	NL	0	TRIAC/ELV	NO					
16-LED	F1L	9	1400	0-10v	YES	<b>Optional</b> 3 3500K		<b>AHA</b> Amber Honey Alabaster <b>BAA</b> Beige Alabaster <b>OAA</b> Opal Alabaster <b>WSP</b> White Smooth Polycarbonate		
	F1K	13	2115	0-10v	YES					
	1E26	NL	0	TRIAC/ELV	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

