

VABW-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Closed top eliminates upward light pollution
- Optional battery backup
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



VABW-15

Height - 15"
Width - 11 1/4"
Depth - 4"



ORDERING INFORMATION

Example: VABW-15-LED-O2B-3-T6-WTP-BB10

VABW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass	WTP White Textured Polycarbonate Optional Lens Material (See Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) 90CRI Consult Factory ES Energy Star listed components 16 Bottom Lens 21 Photocell - <i>See Notes</i> -01 120 volt -02 277 volt Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
15-LED	O2B	15	2000	0-10v	NO					
						Optional 3 3500K				



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

