

# TKGW-LED

## Construction:

- Steel housing and chassis
- Bottom lens is clear tempered glass

## Light Source:

- LED

## Notes:

- Integral mounting plate
- Optional all aluminum construction (painted finish only)
- Photocell - (21) specify voltage 120v or 277v
- Battery backup available in 13" only-increases fixture depth by ¾"
- Down Light only
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

<b>Type:</b>	
<b>Job Name:</b>	



### TKGW-9

Height - 9"  
Width - 8"  
Depth - 5 ½"

### TKGW-13

Height - 13 ½"  
Width - 12"  
Depth - 8 ½"



## ORDERING INFORMATION

**Example: TKGW-13-LED-F2B-3-Z1-CEG**

### TKGW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
9-LED	F2B	12	1180	0-10v	NO	2 3000K 4 4000K	<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder <b>M16</b> Antique Brass <b>P2</b> Brushed Alum <b>P9</b> Brushed Nickel	CEG Clear Tempered Glass	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v Consult Factory  <b>42</b> All Aluminum Construction <b>21</b> Photocell - See Notes -01 120 volt -02 277 volt  <b>90CRI</b> Consult Factory  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes	
13-LED	F2B	12	1180	0-10v	NO	Optional 3 3500K				



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

