

NOVW-LED

Construction:

- Steel chassis
- Diffuser is .125" thick opal alabaster acrylic or optional amber honey, beige alabaster acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots or center lockup for standard J-box
- Open top and bottom
- Optional Battery Backup
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



NOVW-11-LED

Height - 10 3/4"
 Width - 10"
 Depth - 3 1/2"



ORDERING INFORMATION

Example: **NOVW-11-LED-F1H-4-OAA**

NOVW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K			OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
11-LED	F1H	9	1400	0-10v	YES	Optional 3 3500K			Optional Lens Material (see Price List)	ES Energy Star listed components 90CRI Consult Factory Optional Voltage -347V Input voltage to 347v OCCHFB Concealed Occupancy Sensor (O2A Configuration Only) See Sensor Resource Sheet Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	F1O	10	863	TRIAC/ELV	YES				AHA Amber Honey Alabaster	
	F1P	15	1361	TRIAC/ELV	YES				BAA Beige Alabaster	
	O2A	12	1600	0-10v	NO					
	F1J	20	2820	0-10v	YES					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

