

MDAW-6xx-LED

Construction:


- Steel chassis and cage
- Diffuser is impact resistant extruded white acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots
- Top and bottom white acrylic lens - standard
- Optional photocell (21) increases fixture depth 3/4"
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



MDAW-612

MDAW-616

MDAW-626

MDAW-638

MDAW-650

DIM 'A'	M.C.
12"	6"
16"	8"
26"	13"
38"	19"
50"	25"

Type:	
Job Name:	



ORDERING INFORMATION

Example: MDAW-612-LED-O1C-4-Z3-WSA

MDAW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K 5 5000K				
612-LED	O1C	9	1210	0-10v	NO			B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v)
616-LED	O1C	9	1210	0-10v	NO					
626-LED	O2C	18	2420	0-10v	NO					21 Photocell - See Notes -01 120 volt -02 277 volt
638-LED	O3C	27	3630	0-10v	NO					Optional Voltage -347V Input voltage to 347v
650-LED	O4C	36	4840	0-10v	NO			Optional (See Price List) M17 Brass Powder P2 Brushed Alum		Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes

