

PCLH-LED

Construction:

- Steel pan and rings
- Diffuser is white smooth acrylic
- Optional high efficiency white smooth acrylic lens designed for LED light source (WSAHE)

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Canopy mounts to standard J-Box
- Custom stem heights available
- No uplight
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



PCLH-15
 Height - 3 1/4"
 Diameter - 15
 Overall Height - 24"

PCLH-21
 Height - 3 1/4" *3R Option*
 Diameter - 21 1/4
 Overall Height - 24"



ORDERING INFORMATION

Example: PCLH-21-LED-L1A-4-Z1-WSA-1SLM45-21"OAH

Size	LED					Kelvin	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star				
PCLH-15-2R-LED	F1K	13	2115	0-10v	YES	2 3000K 4 4000K	T6 Pewter W2 Gloss White Z1 Satin Bronze Z3 Text Bronze	WSA White Smooth Acrylic	(Suspension Systems) Please list Over All Height 1SLM45 -Single Stem 45 degree swivel
PCLH-15-3R-LED	F1P	15	1361	TRIAC/ELV	YES	Optional 3 3500	Optional (see Price List)	Optional Lens Material (see Price List) WSAHE White Smooth Acrylic High Efficiency	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page
	F1Q	23	2057	TRIAC/ELV	YES				
PCLH-21-2R-LED	L1A	36	4000	0-10v	NO		W1 Yolk W3 Text White B1 Satin Black B2 Text Black T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige		ES Energy Star listed components T24 Title 24/JA8 Compliant (F1P & F1Q configuration only)
PCLH-21-3R-LED									90CRI Consult Factory
									OCCHFA Concealed Occupancy Sensor See <i>Sensor Resource Sheet</i>



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

