

# ORLW-LED

## Construction:

- Steel housing and chassis
- Diffuser is .060" thick white textured polycarbonate

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Keyhole slots or center lockup for standard J-box
- Custom cage styles available
- Open top and bottom for up and down light
- ADA compliant
- Optional Battery Backup
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### ORLW-11-LED

Height - 11"  
Width - 10"  
Depth - 4"

### ORLW-16-LED

Height - 15 1/2"  
Width - 13 7/8"  
Depth - 4"



## ORDERING INFORMATION

Example: **ORLW-16-LED-1FH-4-P2-WTP**

### ORLW

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
11-LED	F1H	9	1400	0-10v	YES	2 3000K 4 4000K  Optional 3 3500K		B1 Satin Black	WTP White Textured Polycarbonate	<b>DIM</b> LED dimming driver (0 - 10v) <b>DIMLD</b> Line Voltage /TRIAC/ELV/120v See Resource Page  <b>ES</b> Energy Star listed components <b>90CRI</b> Consult Factory  Optional Voltage <b>-347V</b> Input voltage to 347v  <b>OCCHFB</b> Concealed Occupancy Sensor (O2A Configuration Only) See Sensor Resource Sheet  <b>Battery Backup Options</b> (Available with 0-10v only) <b>BB10</b> 10 Watts (1170lm) for 90-Minutes
	F1O	10	863	TRIAC/ELV	YES			M13 Anod Silver		
	F1P	15	1361	TRIAC/ELV	YES			T4 Shimmer Gray		
	O2A	12	1600	0-10v	NO			T6 Pewter		
	F1J	20	2820	0-10v	YES			W2 Gloss White		
16-LED	F1H	9	1400	0-10v	YES		<b>Optional Finishes</b> (see Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	W1 Yolk White Z1 Satin Bronze Z3 Text Bronze  AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster		
	F1P	15	1361	TRIAC/ELV	YES					
	O2A	12	1600	0-10v	NO					
	O2C	18	2420	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

