

MEDW-600-LED

Construction:

- Steel housing and chassis
- $\frac{3}{8}$ " Sq Accent bars and rings are extruded aluminum

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots top and bottom
- Solid front shield allowing no forward light
- Down light only complies with Dark Sky requirements
- Optional photocell (21) increases fixture depth 1 $\frac{1}{2}$ "
- BUG Rating: B10U0G0
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components


Type:	
Job Name:	



DESIGN OPTIONS (Choose your cage design)




MERW-A



MERW-B



MERW-C^{D1}



MERW-D



MERW-E




MERW-F^{D1}



MERW-G^{D1}



MERW-H^{D1}



MERW-I



MERW-J



MERW-K^{D1}



MERW-X

Fixture Overall Dimensions

"H" - 12" - 16" - 18" - 26" - 38" - 50"



"W" - 6 $\frac{1}{2}$ "

"D" - 4" 

"D1" - 4 $\frac{3}{8}$ "

"MC" - 6" - 8" - 9" - 13" - 19" - 25"

- See 900 or 1100 Series for other width options



⁽¹⁾ Contact factory for assistance



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 www.lightwayind.com • sales@lightwayind.com



Revision: 06/20/2025

ORDERING INFORMATION

Example: MEDW-626-LED-G-F2B-4-B1

MEDW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K 5 5000K	A B D E F G H I J K X	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter	Optional Cage Accents (See Page 2) Material F Filigree P Perforated Screen M Wire Mesh W Waffle Pattern Style SC Screen Complete CC Center Complete EC Ends Complete CH Center Half OX Custom	DIM LED dimming driver (0 - 10v)
612-LED	F2B	12	1180	0-10v	NO					21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt
616-LED	F2B	12	1180	0-10v	NO					
618-LED	F2B	12	1180	0-10v	NO					
626-LED	F2B	12	1180	0-10v	NO					OCCHFB Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> (0-10v Driver Engine only)
638-LED	F2B	12	1180	0-10v	NO					
650-LED	F2B	12	1180	0-10v	NO					Optional Voltage -347V Input voltage to 347v Battery Backup Options (0-10v Driver Engine only) BB10 10 Watts (1170lm) for 90-Minutes

