

# WMBV-LED

## Construction:

- Steel chassis and decorative band
- Diffuser is white smooth acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup – hardware included
- Vertical or Horizontal mounting
- Open sides with diffused LED light source
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### WMBV-16

Height - 5 1/4"  
Depth - 4"  
Length - 16"

### WMBV-22

Height - 5 1/4"  
Depth - 4"  
Length - 22"



## ORDERING INFORMATION

Example: WMBV-16-LED-U-10W-4-P1-WSA

### WMBV

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
16-LED						2 3000K 4 4000K	B1 Satin Black W2 Gloss White T4 Shimmer Gray T6 Pewter M13 Anod Silver T6 Pewter Z1 Satin Bronze	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory	
	2E26		0	TRIAC/ELV	NO					
22-LED						Optional 3 3500K	Optional (see Price List) M17 Brass Powder P0 Polished Brass P1 Chrome P2 Brushed Alum M16 Antique Brass P9 Brushed Nickel		90CRI Consult Factory	
	2E26		0	TRIAC/ELV	NO					
										Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

