

TUSB-LED

Construction:

- Steel housing and chassis
- Bottom lens is clear smooth acrylic or white frosted acrylic

Post:

- (WP) Select tight knotted cedar direct burial post *standard*. Comes 4x6x60" allowing field to define
- (SP) Optional 4" sq steel post 36" tall with square flange base, cover and anchor bolts.

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Optional Photocell - (21) specify voltage 120v or 277v
- Dark Sky compliant
- UL and CUL listed WET location
- 5-Year Warranty on LED Components
- **Companion Wall Fixture - TUSW**

TUSB-8

Height - 7"

Width - 8 1/4"

Depth - 8 3/8"



Type:	
Job Name:	



ORDERING INFORMATION

Example: TUSB-8-LED-O1A-4-W2-CSA-WP-21-01

TUSB

--	--	--	--	--	--	--

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
8-LED	O1A	6	800	0-10v	NO	2 3000K		B1 Satin Black	CSA Clear Smooth Acrylic WFA White Frosted Acrylic	WP Cedar Post (Standard) SP Steel Post (Optional See Price list) <i>Finish to match fixture</i>
	O2A	12	1600	0-10v	NO	4 4000K		B2 Text Black		
						Optional		Z1 Satin Bronze		
						3 3500K		Z3 Text Bronze		
								W1 Yolk White		
								W2 Gloss White		
								T4 Shimmer Gray		
								M13 Anod Silver		
								T6 Pewter		
								W13 Pearl Beige		
								Optional		
								(See Price List)		
								M17 Brass Powder		
								M16 Antique Brass		
								P2 Brushed Alum		
								P9 Brushed Nickel		
										DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
										42 All Aluminum Construction
										21 Photocell - See Notes
										-01 120 volt
										-02 277 volt
										ES Energy Star listed components
										90CRI Consult Factory



28435 Industry Drive., Valencia, California 91355
00-325-4448 /661-257-0286
www.lightwayind.com • sales@lightwayind.com



Revision: 10/29/2026