

# RMDW-LED

## Construction:

- Steel chassis
- Diffuser is white smooth acrylic

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup – hardware included
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



## RMDW-7-LED

Height - 7"  
Width - 14"  
Depth - 4"



## ORDERING INFORMATION

Example: RMDW-7-LED-O1B-4-WSA-CT

## RMDW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		<b>Deco Trim Only</b> <b>B1</b> Satin Black <b>P0</b> Polished Brass* <b>T4</b> Shimmer Gray <b>T6</b> Pewter <b>W13</b> Pearl Beige  <b>Optional</b> (See Price List) <b>M17</b> Brass Powder <b>P9</b> Brushed Nickel <b>M16</b> Antique Brass <b>P1</b> Chrome* <b>P2</b> Brushed Alum  * Interior Use Only	WSA White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) Dimming to 10% ( <b>Included</b> )  <b>BT</b> Brass Trim <b>CT</b> Chrome Trim <b>DT</b> Deco Trim  Optional Voltage <b>-347V</b> Input voltage to 347v
7-LED	O1B	8	1000	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
www.lightwayind.com • sales@lightwayind.com

