

CALC-LED

Construction:

- Steel housing and steel chassis
- Diffuser is .080" thick white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Optional battery backup - increases depth by 1 1/2"
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



CALC-12

Height - 4"
Width - 11 1/2"

CALC-16

Height - 4"
Width - 15 1/2"



ORDERING INFORMATION

Example: CALC-LED-16-F1Q-4-B1-WTP

CALC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K				
12-LED	F1L	9	1400	0-10v	YES	Optional 3 3500K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page 90CRI Consult factory ES Energy Star listed components	
	F1O	10	863	TRIAC/ELV	YES					
	F1P	15	1361	TRIAC/ELV	YES					
	F1K	13	2115	0-10v	YES					
16-LED	F1K	13	2115	0-10v	YES				Optional Lens Material (see Price List)	OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet (Only available in 20 watt) Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					
	L1A	36	4000	0-10v	NO					
	O2C	18	2420	0-10v	NO					
	2E26		0	TRIAC/ELV	NO			Optional (See Price List) M17 Brass Powder M16 Antique Brass	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

