SUTC-LED

Type:	
Job Name:	

Construction:
- Aluminum pan
- Diffuser is frosted ribbed glass or optional marbleized glass

Light Source:
- LED
- Dimming to 10% **Included**

Notes:
- Keyhole slots for standard J-Box – hardware included
- Optional battery backup
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Shown with Frosted Ribbed Glass & P2 finish

SUTC-16
Height - 7 ¼"
Diameter - 15 ½"
Finial may change height

ORDERING INFORMATION

Example: SUTC-16-LED-F1Q-4-P2-FMG-BB10

SUTC

Size	LED	Watts	Source Lumens	Dimming	Energy Star
16-LED	F1L	9	1400	0-10v	YES
	F1O	10	863	TRIAC/ELV	YES
	F1P	15	1361	TRIAC/ELV	YES
	F1K	13	2115	0-10v	YES
	F1Q	23	2057	TRIAC/ELV	YES

Kelvin
2 3000K
4 4000K

Optional
3 3500K

Cage

Finish
B1 Satin Black
B2 Text Black
Z1 Satin Bronze
Z3 Text Bronze
W1 Yolk White
W2 Gloss White
T4 Shimmer Gray
M13 Anod Silver
T6 Pewter
W13 Pearl Beige

Optional
(See Price List)
M17 Brass Powder
M16 Antique Brass
P2 Brushed Alum
P9 Brushed Nickel

Diffuser
FRG Frosted Ribbed Glass
FMG Frosted Marbleized Glass

Options
DIM LED dimming driver (0 - 10v)
DIMLD Line Voltage /TRIAC/ELV/120v
See Resource Page

ES Energy Star listed components
90CRI Consult Factory

OCCHFA Concealed Occupancy Sensor
See Sensor Resource Sheet

Optional Voltage
-347V Input voltage to 347v

Battery Backup Options
(Available with 0-10v only)
BB10 10 Watts (1170lm) for 90-Minutes

28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286• fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

Revision: 04/20/2021