SAMP-LED

Type:	
Job Name:	

Construction:
- Steel housing and chassis
- Diffuser is white textured polycarbonate
- Optional alabaster acrylic lenses

Light Source:
- LED

Notes:
- Mounts to 3" round pole – fitter included
- Fixture dimensions excluded fitter
- See supplemental spec sheet on website for pole options
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

SAMP-15-LED
Height - 15"
Width - 9"
Depth - 9"

SAMP-22
Height - 22"
Width - 12"
Depth - 12"

ORDERING INFORMATION

Example: SAMP-15-LED-O4B-4-Z1-WTP

SAMP [ ] [ ] [ ] [ ] [ ] [ ] [ ]

Size	LED	Watts	Source Lumens	Dimming	Energy Star
15-LED	1E26		0	TRIAC/ELV	NO
	O4B	29	4000	0-10v	NO
	O4C	36	4840	0-10v	NO
22-LED	O8B	58	8000	0-10v	NO

Kelvin
2 3000K
4 4000K

Optional
3 3500K

Finish
B1 Satin Black
B2 Text Black
Z1 Satin Bronze
Z3 Text Bronze
W1 Yolk White
W2 Gloss White
W3 Text White
T4 Shimmer Gray
M13 Anod Silver
T6 Pewter
W13 Pearl Beige

Optional
(See Price List)
M17 Brass Powder
M16 Antique Brass

Diffuser
WTP White Textured Polycarbonate

Optional Lens Material
(See Price List)

AHA Amber Honey Alabaster
BAA Beige Alabaster
OAA Opal Alabaster

Options
Optional Voltage
-347V Input voltage to 347v

Pole Options
(see supplemental spec sheet on website and price list)

28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286• fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com