

YRBV-LED

Construction:

- Steel chassis and front shield
- Top and bottom diffuser is white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Dimming ballast may be limited with some lamps
- Optional perforated steel top and/or bottom diffuser
- Optional solid top to eliminate up light
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



YRBV-18

Height - 6"
Depth - 4"
Length - 18"

YRBV-24

Height - 6"
Depth - 4"
Length - 24"



ORDERING INFORMATION

Example: YRBV-24-LED-U-O2C-3-W1-WSA

YRBW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) 90CRI Consult Factory
18-LED	O2A	12	1600	0-10v	NO	Optional 3 3500K		Optional (See Price List) M17 Brass Powder		
24-LED	O2C	18	2420	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

