LDWH

Where timeless craftsmanship meets modern design.

The traditional pendant is reimagined with a sophisticated wood trim band, blending natural warmth with contemporary elegance. By incorporating wood into interior applications, this fixture does more than illuminate—it transforms the atmosphere. Wood introduces durability, texture, and a timeless aesthetic, while also enhancing comfort, well-being, and productivity. It's not merely decorative; it's a design element that connects people to nature, enriches mood, and adds character to any space.

Choose from a curated selection of faux wood finishes—Bamboo, Maple, Teak, or Walnut—each offering its own unique grain and tone to complement a wide range of interiors.

Bands available with opaque or semi-translucent bands, allowing you to tailor the glow to your desired ambiance—whether soft and diffused or crisp and defined.

Practical Benefits:

- Low Maintenance: Easily cleaned with a simple wipe of a damp cloth.
- Versatile Styling: Works seamlessly in modern, transitional, or traditional spaces.
- Sustainable Appeal: Faux wood options provide the natural look without the upkeep of real wood.

Design Impact:

Adding wood trim to lighting fixtures introduces warmth, depth, and a sense of craftsmanship. It elevates interiors by balancing functionality with artistry, making the pendant not just a source of light but a focal point of design.







Construction:

- The LDWH features a faux-wood side diffuser, offered with either non-translucent or semi-translucent lens options, surrounding a traditional white smooth acrylic lens to accommodate a wide range of aesthetic and functional design goals.
- Standard light distribution is calibrated to deliver 60% uplight and 40% downlight. For customized distribution configurations, please contact the factory
- The bottom diffuser is crafted from white textured acrylic
- The canopy and housing are built from durable steel and finished with a sleek, powder-coated surface for enhanced protection and visual appeal.

Light Source:

- LED
- Incandescent socket base

Notes:

- Mounting Kit Included for standard J-box
- Multiple canopy and stem options available.
- Custom overall heights available
- Build America, Buy America Act Compliant
- UL and CUL listed **DAMP** location
 - Replaceable Module
 - CRI > 90
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard



















For ceiling flush mount fixture, please see the LDWC

DIFFUSER OPTIONS


















LDWH














LED BASED ORDERING INFORMATION

Example: LDWH-15-LED-F1K-4-W2-DV2-1SLM45-12"OAH-DIM


LDWH

Size	LED					Kelvin	Finish	Side Diffusers	Options
		Watts	Source Lumens	Dimming	Energy Star	1 2700K 2 3000K	See Finish Options Page 5	Maple DV1 Opaque Maple	(Suspension Systems) <mark>Please list Over All Height</mark>
12-LED	F1H	9	1400	0-10v	YES	3 3500K		DT1 Semi-Translucent	1S15 -Single Stem 15 degree swivel
	F10	10	863	TRIAC/ELV	YES	4 4000K 5 5000K		Maple Bamboo	1SLM45 -Single Stem 45 degree swivel 4AC -(4) Aircraft Cable
	F1P	15	1361	TRIAC/ELV	YES			DV2 Opaque Bamboo	3AC -(3) Aircraft Cable
15-LED	F1K	13	2115	0-10v	YES	1		DT2 Semi-Translucent	
	F1P	15	1361	TRIAC/ELV	YES			Bamboo Teak	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v
	F1Q	23	2057	TRIAC/ELV	YES			DV3 Opaque Teak	ES Energy Star listed components
19-LED	L1A	36	4000	0-10v	NO			DT3 Semi-Translucent Teak	T24 Title 24/JA8 Compliant (F10, F1P & F1Q configuration only)
	F1Q	23	2057	TRIAC/ELV	YES			Walnut	(110,111 & 112 configuration only)
24-LED	L1A	36	4000	0-10v	NO			DV4 Opaque Walnut	OCCHFA Concealed Occupancy Sensor
30-LED	O4C	36	4840	0-10v	NO			DT4 Semi-Translucent Walnut	See Sensor Resource Sheet
36-LED	O8C	72	9680	0-10v	NO	-		Walliut	Battery Backup Options
	O12C	107	14520	0-10v	NO				(Available with 0-10v only)
	O12C	107	14520	0-10v	NO				BB10 10 Watts (1170lm) for 90-Minutes








LDWH-E26




	DIM 'A'	DIM 'B'	ОАН
LDWH-12	12.25"	4.5"	12"
LDWH-15	15"	4.5"	12"
LDWH-19	19"	5.25"	12"
LDWH-24	24"	8"	15"
LDWH-30	30"	8"	24"
LDWH-36	36"	8"	24"









INCANDESCENT BASED ORDERING INFORMATION

Example: LDWH-36-8E26-NL-W2-DV2-1SLM45-24"OAH

NL**LDWH**

Size	Socket					Kelvin	Finish	Side Diffusers	Options
		Watts	Source Lumens	Dimming	Energy Star	NL Lamps	See Finish Options Page 5	Maple DV1 Opaque Maple	(Suspension Systems) Please list Over All Height
12	2E26			TRIAC/ELV		provided		DT1 Semi-Translucent	1S15 -Single Stem 15 degree swivel
						by others		Maple	1SLM45 -Single Stem 45 degree swivel
								Bamboo	4AC -(4) Aircraft Cable
15	2E26			TRIAC/ELV				DV2 Opaque Bamboo	3AC -(3) Aircraft Cable
								DT2 Semi-Translucent	
19	3E26			TRIAC/ELV				Bamboo	CF - Center Finial
13	3220			1111110/22				Teak	
								DV3 Opaque Teak	
24	4E26			TRIAC/ELV				DT3 Semi-Translucent	
30	8E26			TRIAC/ELV				Teak	
36								Walnut DV4 Opague Walnut	
								DV4 Opaque Walnut DT4 Semi-Translucent	
								Walnut	
								vvaillut	





FINISHES

Standard Finishes



Premium Finishes - Contact Factory For Pricing



DISCLAIMER:

Colors displayed on your screen may vary slightly from the actual product color due to differences in monitor calibration and lighting conditions. Sample chips are available upon request. **Not all finishes are available with all fixtures. Please consult factory for premium finishes.**



