CRSV-LED

Construction:
- Steel housing and chassis
- Diffuser is white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:
- LED
- Dimming to 10% **Included**

Notes:
- Center lockup – hardware included
- Perforated front panel (PP) reduces front lighting
- Solid top (ST) eliminates up light
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



Length - 16" - 24" - 36" - 48"
Height - 5½"
Depth - 3½"

DIMMABLE

MADE IN AMERICA

ORDERING INFORMATION

Example: CRSV-24-LED-O2C-3-W1-BAA

CRSV [ ] [ ] [ ] [ ] [ ] [ ] [ ]

Size	LED	Watts	Source Lumens	Dimming	Energy Star
16-LED	**O2C**	18	2420	0-10v	NO
24-LED	**O2C**	18	2420	0-10v	NO
36-LED	**O3C**	27	3630	0-10v	NO
48-LED	**O4C**	36	4840	0-10v	NO

Kelvin
- **2** 3000K
- **3** 3500K
- **4** 4000K

Cage

Finish
- **B1** Satin Black
- **B2** Text Black
- **Z1** Satin Bronze
- **Z3** Text Bronze
- **W1** Yolk White
- **W2** Gloss White
- **W3** Text White
- **T4** Shimmer Gray
- **M13** Anod Silver
- **T6** Pewter
- **W13** Pearl Beige

Optional
(See Price List)

- **M17** Brass Powder
- **P2** Brushed Alum
- **P9** Brushed Nickel
- **M16** Antique Brass

Diffuser
- **WTP** White Textured Polycarbonate

Optional Lens Material
(see Price List)
- **AHA** Amber Honey Alabaster
- **BAA** Beige Alabaster
- **OAA** Opal Alabaster

Options
- **DIM** LED dimming driver (0 - 10v) Dimming to 10% (**Included**)
- **PP** Perforated Front Panel
- **ST** Solid Top (No Up Light)

28435 Industry Drive., Valencia, California 91355
800-325-4448 /661-257-0286
www.lightwayind.com • sales@lightwayind.com

Revision: 11/11/2026