MEZW-LED

Geometric detail. Architectural illumination.



A distinctive profile for exterior spaces



A geometric cut-out cage overlays a five-sided acrylic diffuser, bringing texture and visual interest to entries, façades and corridors.

Steel housing and chassis
UV-stabilized, high-impact-resistant DR acrylic
Integral mounting plate for a standard junction box

UL / CUL WET

0-10V DIMMING

4-INCH STANDARD DEPTH

FIVE HEIGHT VARIANTS

Specify the right scale

All models: 5.5 in. wide x 4 in. deep

13 in.	18 in.	26 in.	38 in.	50 in.
MEZW-513	MEZW-518	MEZW-526	MEZW-538	MEZW-550

ADA depth Standard fixture is ADA compliant at 4-inch depth. The optional photocell adds 0.5 inch, increasing depth to 4.5 inches; the photocell configuration exceeds the 4-inch ADA projection limit.

Electrical specifications

Input / driver	120-277V universal standard; integral driver
Light quality	CRI >90 standard; standard 3-step MacAdam binning
Color temperatures	2700K / 3000K / 3500K / 4000K / 5000K
Dimming	0-10V standard, to 10%. TRIAC/ELV on qualifying configurations; consult factory.
LED system	Field-replaceable LED module; lumen maintenance >60,000 hours
Listing	UL and CUL Listed for WET locations
Emergency option	90-minute battery backup on MEZW-526, -538 and -550
Photocell option	120V or 277V; adds 0.5 inch to fixture depth

Consult factory for configuration-specific wattage and source lumens, and other dimming options.

IN CONTEXT

Designed for the approach



Retail and mixed-use exteriors





Hospitality interiors and gathering spaces

Ideal applications include hotel and resort entry façades, multifamily residential buildings, accessible pathways and corridors, retail and mixed-use exteriors, and healthcare campus entries.

MAKE IT YOUR OWN

Finish and configure



Non-VOC powder-coat and low-VOC metal finishing options. Custom finishes available; consult factory. Colors shown are representative.

Built for your project

Made in America, with BABA-compliant options always available. Optional all-aluminum construction enhances corrosion resistance. Confirm the required configuration with the factory.

5-year warranty on LED components
Optional 10-year warranty available.