

# BPRP-LED

## Construction:

- Steel top, bottom and rings
- Cylinder is .125" thick white smooth acrylic

## Light Source:

- LED

## Notes:

- Mounts to 3" round pole – aluminum fitter included
- Fixture dimensions exclude fitter
- See supplemental spec sheet on website for pole options and wall mounting bracket
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### BPRP-12

Height - 12"  
Width - 7 1/4"

### BPRP-16

Height - 16"  
Width - 8 1/2"

### BPRP-21

Height - 21"  
Width - 10"



## ORDERING INFORMATION

Example: **BPRP-16-LED-O4C-4-Z3-WSA-MU**

### BPRP

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K				27 Wall Mount Bracket
12-LED	O4B	29	4000	0-10v	NO	Optional 3 3500K	B1 Satin Black B2 Text Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W1 Yolk W2 Gloss White W3 Text White W13 Pearl Beige Z1 Satin Bronze Z3 Text Bronze	WSA White Smooth Acrylic	Pole Options <i>(see supplemental spec sheet on website and price list)</i>	
	1E26		0	TRIAC/ELV	NO					
16-LED	O4C	36	4840	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					
21-LED	O8B	58	8000	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

